ESPRESSO
COFFEE MACHINES

PRATIKA

Characteristics

EASY SERVICE
Quick access to internal components for fast maintenance

ELECTRONIC AUTO-LEVEL
Automatically fills and maintains the boiler using an electronic level sensor

PLUG & PLAY
Connect, power on, and brew effortlessly

STAINLESS STEEL BOILER
Built for long-lasting performance

Optional

ECO-MODE SYSTEM
Automatically reduces energy consumption after a period of inactivity

PUMP & BOILER DUAL GAUGES
Provide control over coffee extraction and boiler pressure

WOOD COMPONENTS
Walnut group, tap and portafilter handles

acm-company.com
Discover the full range of coffee machines

Technical Data		1 gr - Vibration	1 gr - Rotary
Voltage	V	220-240 1N	220-240 1N
Power input	kW	1100	1100
Pump power	kW	48	100
Boiler capacity	lt	1.5	1.5
Water tank capacity	lt	2.5	Switchable from water tank to a fixed water connection
Net weight	kg	20	22
Gross weight	kg	24	26
Dimensions	cm	25x35x40h	25x35x40h
Packaging dimensions	cm	35x48x57h	35x48x57h

Max cup high 100mm

Versions	1 gr - Vibration	1 gr - Rotary
	1 steam tap	1 steam tap
	1 water tap	1 water tap
	1 one-cup portafilters	1 one-cup portafilters
	1 two-cup portafilters	1 two-cup portafilters
	Available in semi-automatic version	

Standard Colors

Customization of side panels with graphics and colors (on request)

Discover our full range

ROUNDER
professional

EVOLVE
professional

EVOLVE DARK
professional

PRISMA
professional

HOMEY
home

HOMEY DARK
home

Certifications

IEC IECEE CE

AUTOMATIC
COFFEE MACHINES Srl

Via Matteotti, 28
21050 Cairate (VA)

+39 0331 310 411
info@acm-company.it

@acmespresso